


## ACRI-LUX ACRYLIC RUBBING COMPOUND



### TECHNICAL DATA:

<b>Practical Coverage</b>	Depends on targeted surface
<b>Reducer</b>	Use as supplied
<b>Application</b>	Cloth and dry buff
<b>Shelf Life</b>	Minimum of one (1) year under normal condition
<b>Packaging</b>	¼ L, 1L, 4L, and 16L cans

### PRODUCT DESCRIPTION:

It is a fast cutting compound used to restore and improve lacquer and acrylic coated surfaces to its best quality. It also removes scratches, light oxidation, and other defects without sanding.

### PRODUCT HIGHLIGHTS:

Easy to use.  
Restores faded finishes.  
Removes scratches, blemishes and stains.

### RECOMMENDED USE FOR:

Acrylic and lacquer based coatings on automobiles.





#### APPLICATION METHOD:

- Put a small amount of rubbing compound on a dry cloth.
- Rub cloth with small amount of rubbing compound to the desired area.
- Increase rubbing pressure until the compound dries and develops the gloss.
- Clean surfaces with a dry cloth or dry-buff with polishing disc or lamb's wool bonnet.

#### INFORMATION:

**TRITON PRODUCTS** are manufactured from the highest quality raw materials using the most advanced methods. Best results from the superior product are attained when these preparation and application instructions are followed carefully.

For more information on this guide or on any Triton coating product please contact us at 8645-6203 or email us at [tsr.tritonpaints@gmail.com](mailto:tsr.tritonpaints@gmail.com) or [roosevelt.chemical.inc@gmail.com](mailto:roosevelt.chemical.inc@gmail.com)



Tel. Nos. 7758-6245 | 7900-9642 | 8645-6625 | 8645-1089  
8645-2152 | 8645-3435 | 8645-2159 | 8645-3425

FAX: 8645-3425

Cel. Nos. 0908-127-1200 | 0920-828-1221 | 0917-823-3986  
0995-019-1312 | 0923-462-2434

Marketing Dept. 8645-6203 | 0915-644-0036 | 0923-244-3239

**ROOSEVELT CHEMICAL INC.**  
73 F. MARIANO AVE., BO. DELA PAZ, PASIG CITY, PHILIPPINES