


ACRI-LUX RUBBERIZED UNDERBODY COATING BLACK



FLEXIBLE ∞ ANTI-RUST PROTECTION

TECHNICAL DATA:

Drying Time	
Surface dry	2 hours
Recoating	2 hours
Dry Through	overnight
Application	Brush or spray
DFT (approx.)	1- 1.50 mil/ coat
Coverage	25- 30 m2 / 4L/ coat
Reducer	½ liter of Triton Paint Thinner per ½ liter of ACRI-LUX Rubberized Underbody Coating Black
Shelf-life	Minimum one (1) year under normal conditions
Packaging	1L and 4L

PRODUCT DESCRIPTIONS:

It is a premium and durable enamel-based underbody protective paint that is tack-free and fast drying. It produces a highly adhesive coating that is abrasion resistant, and provides excellent protection against stone damage and corrosion on the underbody of automobile.

PRODUCT HIGHLIGHTS:

- ✓ Top and durable finish
- ✓ Soundproof property
- ✓ Repels moisture formation





INFORMATION:

TRITON PRODUCTS are manufactured from the highest quality raw materials using the most advanced methods. Best results from the superior product are attained when these preparation and application instructions are followed carefully.

For more information on this guide or on any Triton coating product please contact us at 8645-6203 or email us at tsr.tritonpaints@gmail.com or roosevelt.chemical.inc@gmail.com



Tel. Nos. 7758-6245 | 7900-9642 | 8645-6625 | 8645-1089
8645-2152 | 8645-3435 | 8645-2159 | 8645-3425

FAX: 8645-3425

Cel. Nos. 0908-127-1200 | 0920-828-1221 | 0917-823-3986
0995-019-1312 | 0923-462-2434

Marketing Dept. 8645-6203 | 0915-644-0036 | 0923-244-3239

ROOSEVELT CHEMICAL INC.
73 F. MARIANO AVE., BO. DELA PAZ, PASIG CITY, PHILIPPINES