

DURACOAT 100% PURE ACRYLIC LATEX



TECHNICAL DATA:

Specific Gravity	0.90- 1.25±0.05 k/ l (depends on color and finish)
Viscosity	100± 5 KU
DFT (approx.)	40-50 microns / coat
Coverage	25 - 30 m ² / 4 L/ coat
Drying Time	
Surface dry	30 minutes
Recoating	2 hours
Dry Through	4- 5 hours
Color	Refer to DURACOAT Color Chart
Finish	Gloss, Semi-gloss, Flat & Satin
Reducer	Thin with water up to 5% max.
Application	Brush, roller, spray
Shelf Life	Minimum of one (1) year under normal condition
Packaging	1L, 4L, 16L

PRODUCT DESCRIPTION:

A premium brand of 100% pure acrylic water-based paint with excellent hiding, durability, UV resistant, non-lead and dirt pick-up resistant properties.

PRODUCT HIGHLIGHTS:

Fast drying, sophisticated finished, weather resistant and environmental friendly.

RECOMMENDED FOR:

Exterior and interior walls for Residential, Institutional, Warehouses, Manufacturing, etc.

RECOMMENDED SUBSTRATES:

Concrete, bricks, plaster, stucco & properly primed wood.





METHOD OF APPLICATION:

Surface Preparation

- Let it cure for 14 days to 28 days under normal weather condition before painting
- Treat surface with **Triton Concrete Neutralizer** and let it stand overnight. Sand surface to remove crystal-like formations, rinse thoroughly and dry for twenty-four (24) hours, before paint application.

Paint Application for New Concrete

- Apply one (1) coat of **Duracoat Acrylic Concrete Primer Sealer White** as primer and let it dry for one (1) hour.
- **(Optional)** Level any surface imperfection with **Duracoat Acrylic Concrete Putty** and let it dry completely for two (2) hours before sanding.
- Apply two (2) coats of **Duracoat 100% Pure Acrylic Latex** with an interval of two (2) hours each coat.

Paint Application for Old Surfaces (with Existing Paint)

- Use mechanical and or manual sanding to strip all existing paint.
- Clean surface to remove grease, oil, dust, and all other contaminants. Sand to improve surface's adhesion.
- Apply one (1) coat of **Duracoat Acrylic Concrete Primer Sealer White** and let it completely dry for one (1) hour.
- Apply two (2) coats of **Duracoat 100% Pure Acrylic Latex** with an interval of two (2) hours each coat.

INFORMATION:

TRITON PRODUCTS are manufactured from the highest quality raw materials using the most advanced methods. Best results from the superior product are attained when these preparation and application instructions are followed carefully.

For more information on this guide or on any Triton coating product please contact us at 8645-6203 or email us at tss.tritonpaints@gmail.com or roosevelt.chemical.inc@gmail.com

