

## ODOUR-FRESH PREMIUM ODOUR-LESS ANTI-BACTERIAL LATEX PAINT



### TECHNICAL DATA:

Color	Refer to Odour- Fresh Color Chart
Finish	Matte
Specific Gravity	1.10 ± 0.05 k/l (depends on the color)
Viscosity	100 ± 0.05 KU
Drying Time Surface dry Recoating Dry Through	30 minutes 2 hours 4-5 hours
Application	brush, roller, spray
DFT (approx.)	40-50 microns/ coat
Coverage	25 30 m2 / 4L/ coat
Reducer	Thin with water up to 5% maximum
Shelf-life	Minimum one (1) year under normal conditions
Packaging	1L, 4L, 16L

### PRODUCT DESCRIPTION:

It is 100% acrylic water-based paint formulated with anti-bacterial properties that inhibits microbial growth of any disease causing bacteria on the applied surfaces. It does not emit unpleasant smell once dry.

### PRODUCT HIGHLIGHTS:

Durable, fast drying, low VOC (Volatile Organic Compound), non-lead, suitable for areas that requires good hygienic conditions.

### RECOMMENDED USE FOR:

Interior application.

### RECOMMENDED SUBSTRATE:

Concrete and Masonry.





## METHOD OF APPLICATION:

### Surface Preparation

- Let it cure for 14 days to 28 days under normal weather condition before painting.
- Treat surface with **Triton Concrete Neutralizer** and let it stand overnight. Sand surface to remove crystal-like formations, rinse thoroughly and dry for twenty-four (24) hours, before paint application.

### Paint Application for New Concrete

- Apply one (1) coat of **DURACOAT Acrylic Concrete Primer Sealer White** or **TRITON Flat Latex White** as primer and let it dry for one (1) hour.
- **(Optional)** Level any surface imperfection with **DURACOAT Acrylic Concrete Putty** and let it dry completely for two (2) hours before sanding.
- Apply two (2) coats of **DURACOAT 100% Pure Acrylic Latex** with an interval of two (2) hours each coat.

### Paint Application for Old Surfaces (with existing Paint)

- Use mechanical and or manual sanding to strip all existing paint.
- Clean surface to remove grease, oil, dust, and all other contaminants. Sand to improve surface's adhesion.

- Apply one (1) coat of **DURACOAT Acrylic Concrete Primer Sealer White** or **TRITON Flat Latex White** as primer and let it completely dry for one (1) hour.
- Apply two (2) coats of **ODOUR-FRESH Premium Odour-less Anti-Bacterial Latex Paint** as topcoat with an interval of two (2) hours each coat.

## INFORMATION:

**TRITON PRODUCTS** are manufactured from the highest quality raw materials using the most advanced methods. Best results from the superior product are attained when these preparation and application instructions are followed carefully.

For more information on this guide or on any Triton coating product please contact us at 8645-6203 or email us at [tsr.tritonpaints@gmail.com](mailto:tsr.tritonpaints@gmail.com) or [roosevelt.chemical.inc@gmail.com](mailto:roosevelt.chemical.inc@gmail.com)

