



## TRITON EPOXY REDUCER



### TECHNICAL DATA:

Specific Gravity	0.80 k/l
Color	Water white
Odor	Aromatic
Packaging	1L, 4L, 16L

### PRODUCT DESCRIPTION:

High quality blends of organic solvent used to bring out the finest quality finished product of epoxy-based paints during application.

### PRODUCT HIGHLIGHTS:

High reducing power, aids in better consistency and avoid surface defects while application.

### RECOMMENDED FOR:

As thinner or reducer for **TRITON EPOXY PRIMERS** and **TRITON EPOXY ENAMELS**





## APPLICATION:

### Application Method

Spray- Mix three (3) parts of epoxy-based paint, one (1) part of catalyst; and two (2) parts of **TRITON EPOXY REDUCER**

Paint Brush/ Roller Brush- Mix three (3) parts of epoxy-based paint; one (1) part of catalyst and one (1) part of **TRITON EPOXY REDUCER**.

Upon mixing, allow ten to fifteen (10-15) minutes induction time before

## INFORMATION:

**TRITON PRODUCTS** are manufactured from the highest quality raw materials using the most advanced methods. Best results from the superior product are attained when these preparation and application instructions are followed carefully.

For more information on this guide or on any Triton coating product please contact us at 8645-6203 or email us at [tsr.tritonpaints@gmail.com](mailto:tsr.tritonpaints@gmail.com) or [roosevelt.chemical.inc@gmail.com](mailto:roosevelt.chemical.inc@gmail.com)

