



TRITON GYPSUM PUTTY



TECHNICAL DATA:

Appearance	Liquid type
Color	White
Specific Gravity	1.75±0.05 k/l
Recommended Thickness	1-3 mm/application
Coverage	8-10 m ² / gal/ 1mm
Setting Time	30 minutes- 1 hour (depends on the weather condition)
Recoating	1-2 hours
Curing Time	12-48 hours (depends on the weather condition)
Pot Life	1-2 hour
Tools	Putty knife or steel trowel
Shelf Life	Minimum of one (1) year under normal condition
Packaging	Available in 4L, 16 L

PRODUCT DESCRIPTION:

TRITON GYPSUM PUTTY is a high quality acrylic based, non-toxic plaster used for patching holes, joints and as finishing renders for drywalls.

PRODUCT HIGHLIGHTS:

Ready to use putty for easy application, with minimal shrinkage, good sand ability and paint compatibility.

RECOMMENDED FOR:

For interior walls, ceilings, beams, façade etc.

RECOMMENDED SUBSTRATE:

Wooden surfaces, Drywalls.





APPLICATION:

Surface Preparation

Clean surface in order to eliminate dirt and other foreign matter.

Mixing and Application

Use putty knife or steel trowel in applying the mixture thinly on the surface.

Press the putty knife's edge firmly or steel trowel on the surface when applying **TRITON GYPSUM PUTTY**.

Let it dry for 1-2 hours before recoating. Let it dry for 24 hours before application of topcoats.

NOTE: TRITON GYPSUM COMPOUND can be used to repair cracks and dents on the interior wall and cure for at least 1-2 hours before applying **TRITON GYPSUM PUTTY**.

Should be applied on bare, unpainted surfaces.

INFORMATION:

TRITON PRODUCTS are manufactured from the highest quality raw materials using the most advanced methods. Best results from the superior product are attained when these preparation and application instructions are followed carefully.

For more information on this guide or on any Triton coating product please contact us at 8645-6203 or email us at tsr.tritonpaints@gmail.com or roosevelt.chemical.inc@gmail.com

